

Raci Spacer Options: **Large**

Type E and H 25, 41, 60, 75, 90, 110 and 130 mm					
O.D. range inches		O.D. range mm		No. of elements to make a ring	
min	max	min	max	E	H
16.58	18.30	421	465	4	1
18.35	20.86	466	530	5	-
20.91	24.80	531	630	6	-
24.84	28.74	631	730	7	-
28.78	32.67	731	830	8	-
32.29	35.82	820	910	9	-
35.83	40.55	910	1030	10	-
40.59	45.62	1031	1159	11	-
45.67	53.54	1160	1360	13	-
53.58	62.99	1361	1600	15	-
63.03	70.82	1601	1799	17	-
70.87	83.07	1800	2110	20	-
83.11	95.66	2111	2430	23	-
95.71	112.59	2431	2860	27	-
112.64	134.40 *1	2861	3414	32	-
Elements	Runner Height In.	Max Load Per Ring			
		Lbs		Kg	
E/H 25, 41, 60	0.98, 1.61, 2.36	11000		5000	
E/H 75	2.95	8800		4000	
E/H 90	3.54	9000		4100	
E/H 110	4.33	7600		3450	
E/H 130	5.11	7150		3250	

*1 for O.D. larger than 134" (3400) please contact your distributor